

EMERGENSEE™ **SURF**

D40 LED - SURFACE MOUNTED NON-MAINTAINED EMERGENCY LIGHT

Bright and low maintenance, the EmergenSee™ Surf represents a versatile, safe, effective and easy-to-install emergency lighting solution that can be depended upon when it is needed the most.

The robust design offers mounting versatility on solid surfaces with ample internal space to conceal excess cable and can be used in almost all internal general applications including offices, shopping centres, commercial properties, and residential buildings.



Available as:



SYNTHIUM™ nanotechnology is an advanced environmentally sustainable energy development that offers extended battery life, low cost of ownership, enhanced performance and improved safety.




Technical Specifications

| | | |
|-------------|-------------------------------|--|
| Item | Part Number | EMS-SURF |
| | Description | D40 LED Surface Mounted Non-Maintained Emergency Light c/w Synthium™ Battery |
| Input | Voltage & Frequency | 230VAC ; 50Hz |
| | Installation | Terminal block, 20mm ² cable entry |
| Output | Light Source | High performance 3W LED - lifetime warranty |
| | Mode of Operation | Non-Maintained |
| | Power Consumption | 2W (standby) |
| | Emergency Duration | > 120 minutes |
| Controls | Charger | 16hr intelligent 3-stage charger with Synthium™ battery management system |
| | Protection | Overcharge, low voltage disconnect, overcurrent, short circuit |
| | Testing Facility | Manual test switch |
| | Indicators | Battery charger green LED |
| Physical | Construction | Folded sheet metal, powder coat white |
| | Mounting | Surface mounted - ceiling |
| | Dimensions L x W x H | 215mm x 170mm x 70mm |
| | IP Rating | IP20 |
| | Weight | 2.0kg |
| | Warranty | 5 years |
| Environment | Operating Temperature | 1° to 40°C |
| | Relative Humidity | 0 to 95% |
| Compliance | Standards | RCM / EMC, AS/NZS 2293, AS/NZS 60598.1 |
| | AS/NZS 2293 Classification | C0 D40 C90 D40 |
| Accessories | STAR™ Self-Test and Reporting | P/N: EMS-SURF/ST |
| | DALI-compatible | P/N: EMS-SURF/DL |
| | SYNECTIX™ RF Wireless | P/N: EMS-SURF/RF |
| | Replacement Battery | P/N: BAT-ONE: Synthium™ LiFePO ₄ |

NOTE: Product specifications subject to change without prior notice due to ongoing product improvement policy and changes to industry standards.

Dimensions



AS/NZS 2293.1:2018 Spacing Table

| SPACING TABLE | MOUNTING HEIGHT (m) | | | | | | | | |
|---------------------|---------------------|------|------|------|------|------|------|------|------|
| | 2.1 | 2.4 | 2.7 | 3.0 | 4.0 | 5.0 | 6.0 | 8.0 | 10.0 |
| NATA Classification | | | | | | | | | |
| C0 - D40 | 11.5 | 13.2 | 14.8 | 16.5 | 20.1 | 21.2 | 22.1 | 23.0 | 23.0 |
| C90 - D40 | 11.5 | 13.2 | 14.8 | 16.5 | 20.1 | 21.2 | 22.1 | 23.0 | 23.0 |

Distributed By:

